

Camoplast[®]

DURABUILT[™]



**AGCO
CHALLENGER
TRACK
TRACTORS**



DURABUILT™

FOR AGCO CHALLENGER

MT700 AND MT800 SERIES



DURABUILT™ track technology from Camoplast® is an integral part of CHALLENGER's MT700 and MT800 series tractors. Choose DURABUILT tracks to meet all of your requirements in any type of agricultural environment.

AGCO COUNTS ON DURABUILT FROM CAMOPLAST. YOU SHOULD TOO.

MT700 SERIES



DURABUILT™ 3500

MOST POPULAR HIGH DURABILITY TRACK

The Durabuilt 3500 series meets or exceeds original OEM track specifications. This track is appropriate for use in all primary and secondary rowcrop / tillage operations, and offers increased carcass thickness and tread height for additional service life. It is the typical choice for most average sized farming operations.

Note: The Durabuilt 3500 series are not recommended for construction usage. If machine is used in construction or is involved in frequent roading operations or high pull on hard ground, use the Durabuilt 5500 series to gain the substantial durability benefits of these tracks.

DURABUILT™ 5500

PREMIUM FEATURE HEAVY DUTY TRACK

The Durabuilt 5500 series includes all the best features of the 3500 series, plus adds more rubber and more steel to meet the requirements of the most demanding applications. This track is designed for use in both agricultural or construction applications, and is the typical choice for high hour farming operations, rental fleets, and customers with high roading requirements.

Note: For construction applications, we offer two specific scraper tracks in 30" and 36" widths, optimized for use with scraper pans.

MT800 SERIES



TRACK SELECTOR GUIDE - AVAILABLE WIDTHS

MT700 (348")

14"

The 14" track is used for special rowcrop work, where width is the primary consideration. These narrow tracks are subject to the most demanding alignment and material loading conditions. The tracks include a directional tread pattern which requires a LH and RH track version. This 14" width is only for use with the narrow width wheel package. - *Note: This width is not recommended for primary tillage work. If primary tillage work is also done with your machine, then one should switch to 25" or 30" tracks and wider wheel package for these applications.*

SERIES	TYPE	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
				# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
5500	Ag	655-1408		46RH	3.1	2.5	7.8	46	5.5	1.61 (41 mm)	4
5500	Aq	655-1409		46LH	3.1	2.5	7.8	46	5.5	1.61 (41 mm)	4

16"

The 16" track is also used for special purpose rowcrop work, where track width is the primary consideration. These tracks are subject to the most demanding alignment and material loading conditions. Both the Durabuilt 3500 and 5500 are appropriate choices for deep bed applications, where carcass life may be the limiting factor. Proper track series selection is highly dependent on knowledge of the application severity. The 695-1623 and 695-1624, 3500 series tracks, offer low profile treads for use on hard surfaces or for applications requiring reduced ground disturbance. All 16" widths include a directional tread pattern which requires a LH and RH track version. The 16" width is only for use with the narrow width wheel package. - *Note: This width is not recommended for primary tillage work. If primary tillage work is also done with your machine, then one should switch to 25" or 30" tracks and wider wheel package for these applications.*

SERIES	TYPE	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
				# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	Ag	635-1625		46RH	2.8	1.6	7.8	46	4.7	1.45 (37 mm)	4
3500	Ag	635-1626		46LH	2.8	1.6	7.8	46	4.7	1.45 (37 mm)	4
3500	SpcAp	695-1623		65RH	1.6	2.8	5.5	46	4.7	1.45 (37 mm)	4
3500	SpcAp	695-1624		65LH	1.6	2.8	5.5	46	4.7	1.45 (37 mm)	4
5500	Ag	655-1621		46RH	3.1	2.5	7.8	46	5.5	1.61 (41 mm)	4
5500	Ag	655-1622		46LH	3.1	2.5	7.8	46	5.5	1.61 (41 mm)	4

18"

The 18" track is used for general rowcrop work. It has a good balance of performance, flotation, and wear life. The track may also be used for light primary and secondary tillage work. The 695-1818, 3500 series track, offers low profile treads for use on hard surfaces or for applications requiring reduced ground disturbance. This 18" width is only for use with the medium width wheel package.

SERIES	TYPE	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
				# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	Ag	635-1815		92	2.8	1.6	7.8	46	4.7	1.34 (34 mm)	3
3500	SpcAp	695-1818		130	1.6	2.8	5.5	46	4.7	1.34 (34 mm)	3
5500	Ag	655-1817		92	3.1	2.5	7.8	46	5.5	1.61 (41 mm)	4

MT800 (392")

18"

The 18" track is used for general rowcrop work using the MT835 and MT845 tractor models (not recommended for the larger models). The track may also be used for light primary and secondary tillage work. This 18" width is only for use with the medium width wheel package.

SERIES	TYPE	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
				# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
5500	Ag	656-1816		100	3.1	2.5	8	52	5.5	1.61 (41 mm)	4

27.5"

The 27.5" width is recommended for use where width restrictions are the primary consideration. These tracks can be used in all primary and secondary tillage operations. This 27.5" width is only for use with wide width wheel package.

SERIES	TYPE	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
				# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	Ag	636-2708		100	2.8	1.6	8	52	4.7	1.34 (34 mm)	3
5500	Ag	656-2707		100	3.1	2.5	8	52	5.5	1.61 (41 mm)	4

20"

The 20" track is used for special purpose rowcrop work. This track is only for use with the medium width wheel package.

SERIES	TYPE	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
				# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	Ag	635-2004		92	2.8	1.6	7.8	46	4.7	1.34 (34 mm)	3
5500	Ag	655-2005		92	3.1	2.5	7.8	46	5.5	1.61 (41 mm)	4

25"

The 25" track is the preferred width for most primary and secondary tillage work. This width provides a good balance of flotation and ground penetration to get the most power to the ground. The extra width provides additional treadbar life, as well as, less berming during turns over the narrower track offerings. The 695-2520, 3500 series track, offers low profile treads for use on hard surfaces or for applications requiring reduced ground disturbance. Two, 5500 series tracks are available. The 655-2522 should be used in applications requiring additional roading life and improved ride. The 655-2523 should be used in agricultural applications where additional cleanout and ground penetration is desired. The 25" width is for use with the medium and wide width wheel packages.

SERIES	TYPE	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
				# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	Ag	635-2521		92	2.8	1.6	7.8	46	4.7	1.34 (34 mm)	3
3500	SpcAp	695-2520		130	1.6	2.8	5.5	46	4.7	1.34 (34 mm)	3
5500	Ag	655-2522		92	3.1	2.5	7.8	46	5.5	1.61 (41 mm)	4
5500	Ag	655-2523		92	2.8	1.6	7.8	46	5.5	1.61 (41 mm)	4

30"

The 30" track is the choice for any application sensitive to compaction or for additional flotation to minimize berming during turns. The 30" width is only for use with the wide width wheel package.

SERIES	TYPE	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
				# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	Ag	635-3028		92	2.8	1.6	7.8	46	4.7	1.45 (37 mm)	4
5500	Ag	655-3030		92	3.1	2.5	7.8	46	5.5	1.61 (41 mm)	4

All Dimensions in inches unless otherwise noted.

30"

The 30" width is preferred width for the MT800 as it offers a good balance of flotation, penetration, and minimized berming in turns. This track width is only for use with wide width wheel package. - *Note: 696-3017 is the only track recommended for construction applications.*

SERIES	TYPE	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
				# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	Ag	636-3029		100	2.8	1.6	8	52	4.7	1.34 (34 mm)	3
5500	Ag	656-3031		100	3.1	2.5	8	52	5.5	1.61 (41 mm)	4
5500	Scraper	696-3017	501186D1	100	2.2	2.8	8	52	5.5	1.61 (41 mm)	4

36"

The 36" width offers the most in flotation capabilities. This track width is only for use with wide width wheel package. - *Note: 696-3605 is the only track recommended for construction applications.*

SERIES	TYPE	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
				# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	Ag	636-3621		100	2.8	1.6	8	52	4.7	1.45 (37 mm)	4
5500	Ag	656-3622		100	3.1	2.5	8	52	5.5	1.61 (41 mm)	4
5500	Scraper	696-3605	501196D1	100	2.2	2.8	8	52	5.5	1.61 (41 mm)	4

THE INDUSTRY STANDARD



The Camoplast Tracks Systems Group designs, engineers, and manufactures rubber tracks, undercarriage components and systems for the agricultural sector around the globe. Durabuilt tracks from Camoplast have earned a position as the industry standard for the most demanding applications and environments. These tracks are the culmination of nearly 50 years of research and development by the world's leading rubber track experts. Every day, our track designs demonstrate proven reliability for the most prominent OEM names in the agricultural industry.

Authorized Camoplast Distributor:

©2008 Camoplast Inc. All rights reserved. ® and TM are trademarks of Camoplast Inc. Challenger® is a registered trademark of Caterpillar Inc. and used under license by AGCO Corporation.

Camoplast Inc. reserves the right to change or discontinue any specifications, designs, features, models or accessories shown or indicated without notice.

Camoplast sells only through authorized dealers and distributors. Contact your local dealer for pricing and availability.

PRINTED IN CANADA CPB-453 Agco MT700 and MT800

TO VIEW ALL CAMOPLAST HAS TO OFFER
IN TRACKS VISIT OUR WEBSITE

camoplast.com

