

Camoplast[®]

DURABUILT[™]



**JOHN
DEERE
TRACK
TRACTORS**



DURABUILT™ FOR JOHN DEERE 8000T and 9000T SERIES

DURABUILT™ track technology from Camoplast® is an integral part of JOHN DEERE's 8000T and 9000T series agricultural tractors. Choose DURABUILT tracks to meet all your requirements in any type of agricultural environment.

JOHN DEERE COUNTS ON DURABUILT FROM CAMOPLAST. YOU SHOULD TOO.

8000T, 8010T, 8020T, 8030T SERIES



9000T, 9010T, 9020T SERIES



9030T SERIES



DURABUILT™ 2500

GENERAL PURPOSE ECONOMY TRACK

The Durabuilt 2500 series is a general purpose agricultural track intended for light to medium agricultural applications. It is the typical choice for customers with low annual usage, or in situations in which price is the primary purchasing driver, and offers similar performance to most competitive products.

DURABUILT™ 3500

MOST POPULAR HIGH DURABILITY TRACK

The Durabuilt 3500 series is the standard OEM factory installed track. This track is appropriate for use in all primary and secondary rowcrop / tillage operations, and offers increased carcass thickness and tread height for additional service life. It is the typical choice for most average sized farming operations.

DURABUILT™ 5500

PREMIUM FEATURE HEAVY DUTY TRACK

The Durabuilt 5500 series includes all the best features of the 3500 series, plus adds more rubber and more steel to meet the requirements of the most demanding applications. This track is designed for use in both agricultural or construction applications, and is the typical choice for high hour farming operations, rental fleets, and customers with high roading requirements.

Note: The Durabuilt 2500 and 3500 series are not recommended for construction usage. If machine is used in construction or is involved in frequent roading operations or high pull on hard ground, use the Durabuilt 5500 series to gain the substantial durability benefits of these tracks.



TRACK SELECTOR GUIDE - AVAILABLE WIDTHS

8000T, 8010T, 8020T, 8030T SERIES (324")

16"

The 16" width is used for special purpose rowcrop work. These tracks are subjected to the most demanding alignment conditions and material loading. The Durabuilt 2500 is an excellent choice for general rowcrop work while the Durabuilt 3500 and 5500 are appropriate choices for multi-crop bed applications. - Note: 5500 track uses an exclusive directional tread which requires a LH and RH track selection. 16" tracks are not recommended for continuous primary tillage work or for construction applications.

SERIES	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
			# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
2500	621-1607	R246868	96	2.1	2.65	6.9	48	4.1	1.22 (31 mm)	3
3500	631-1608	R241742	96	2.6	2.25	6.9	48	4.1	1.34 (34 mm)	3
5500	651-1604	R222974	48 RH	2.6	2.25	6.9	48	4.7	1.61 (41 mm)	4
5500	651-1605	R222975	48 LH	2.6	2.25	6.9	48	4.7	1.61 (41 mm)	4

25"

The 25" track is the preferred width for most primary and secondary tillage work. This width provides a good balance of flotation and penetration to get the most power to the ground. The extra width also provides longer tread life and improved ride over the narrower track offerings. - Note: For maximum tread life and best ride, this track should be used with the wide midroller wheel package.

SERIES	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
			# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
2500	621-2510	R246870	96	2.1	2	6.9	48	4.1	1.14 (29 mm)	3
3500	631-2509	R241745	96	2.6	1.5	6.9	48	4.1	1.26 (32 mm)	4
3500**	631-2503	R220829	78	2.6	1.5	8.3	48	4.1	1.26 (32 mm)	4
5500	651-2504	R241750	96	2.6	2.25	6.9	48	4.7	1.61 (41 mm)	4

18"

The 18" track is the best choice for general rowcrop work as well as light primary and secondary tillage. It has a good balance of performance, flotation and wear life. - Note: 18" tracks are not recommended for continuous primary tillage work or for construction applications.

SERIES	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
			# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
2500	621-1806	R246869	96	2.1	2	6.9	48	4.1	1.14 (29 mm)	3
3500	631-1803	R241743	96	2.6	1.5	6.9	48	4.1	1.26 (32 mm)	4
5500	651-1804	R222976	96	2.6	2.25	6.9	48	4.7	1.61 (41 mm)	4

30"

The 30" track is a general purpose width for any kind of primary and secondary tillage work. The track provides additional flotation and minimizes soil disturbance and berming during turns. - Note: For maximum tread life and best ride, this track should be used with the wide midroller wheel package.

SERIES	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
			# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	631-3012	R241747	96	2.6	1.5	6.9	48	4.1	1.26 (32 mm)	4
3500**	631-3001	R220830	78	2.6	1.5	8.3	48	4.1	1.26 (32 mm)	4
5500	651-3002	R241751	96	2.6	2.25	6.9	48	4.7	1.61 (41 mm)	4

** Special order only - special use in gumbo or extreme muddy conditions. Due to wider pitch, this track will not ride as smooth as a standard 3500 series.

9000T, 9010T, 9020T SERIES (378")

30"

The 30" track is the most common overall width and is excellent for use in any kind of primary and secondary tillage work.

SERIES	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
			# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	633-3019	R257977	92	2.8	1.6	8.2	54	4.5	1.45 (37 mm)	4
5500	653-3010	R241748	92	2.9	2.7	8.2	54	5.25	1.61 (41 mm)	4

36"

The 36" track minimizes compaction, reduces berming during turns and provides additional tread life. The optimized tread shape allows for even wear out to the edge of the track.

SERIES	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
			# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	633-3606	R257978	92	2.8	1.6	8.2	54	4.5	1.45 (37 mm)	4
5500	653-3601	R241749	92	2.9	2.7	8.2	54	5.25	1.61 (41 mm)	4

9030T SERIES (387")

30"

The 30" track is the best overall width for any kind of primary or secondary agricultural tillage work.

SERIES	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
			# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	633-3022	R242791	88	2.6	2.2	8.8	50	4.5	1.45 (37 mm)	4
5500	653-3021	R242793	88	2.9	2.7	8.8	50	5.3	1.61 (41 mm)	4

36"

The 36" track minimizes compaction, reduces berming during turns and provides additional tread life. The optimized tread shape allows for even wear out to the edge of the track.

SERIES	CAMOPLAST PART #	OEM PART #	TREADBARS				GUIDES		CARCASS	
			# TREADS	HEIGHT	TIP WIDTH	PITCH	# GUIDES	LENGTH	THICKNESS	PLY LAYERS
3500	633-3609	R242792	88	2.6	2.2	8.8	50	4.5	1.45 (37 mm)	4
5500	653-3608	R242794	88	2.9	2.7	8.8	50	5.3	1.61 (41 mm)	4

THE INDUSTRY STANDARD



The Camoplast Tracks Systems Group designs, engineers, and manufactures rubber tracks, undercarriage components and systems for the agricultural sector around the globe. Durabuilt tracks from Camoplast have earned a position as the industry standard for the most demanding applications and environments. These tracks are the culmination of nearly 50 years of research and development by the world's leading rubber track experts. Every day, our track designs demonstrate proven reliability for the most prominent OEM names in the agricultural industry.

Authorized Camoplast Distributor:

©2008 Camoplast Inc. All rights reserved. ® and TM are trademarks of Camoplast Inc.
©2008 Deere & Company. All Rights Reserved.

Camoplast Inc. reserves the right to change or discontinue any specifications, designs, features, models or accessories shown or indicated without notice.

Camoplast sells only through authorized dealers and distributors.
Contact your local dealer for pricing and availability.

PRINTED IN CANADA CPB-452 JD 8T and 9T

TO VIEW ALL CAMOPLAST HAS TO OFFER
IN TRACKS VISIT OUR WEBSITE

camoplast.com

