



## Leading the way

With more than 10 million tracks produced since 1958, Camoplast is the leading brand of high-performance tracks. Camoplast relies on exclusive state-of-the-art manufacturing capabilities and the largest R&D team in the industry to lead the way in the development and manufacturing of high-quality tracks delivering superior value.

Indeed, Camoplast's singular expertise has made its tracks the original equipment brand preferred by vehicle manufacturers. As a global producer, Camoplast is committed to leading the way in the development and manufacturing of high-quality tracks delivering superior value. This commitment is backed by an unrivaled warranty and supported by best-in-class customer service.

Visit our website for information on our products or e-mail us at [flexhaul@camoplast.com](mailto:flexhaul@camoplast.com)

[camoplast.com](http://camoplast.com)


Camoplast authorized distributor:

© 2011 Camoplast Solideal Inc. All rights reserved. ® and TM are trademarks of Camoplast Solideal Inc.

Camoplast Solideal Inc. reserves the right to change or discontinue any specifications, designs, features, models or accessories shown or indicated without notice.

Camoplast sells only through authorized dealers and distributors. Contact your local dealer for pricing and availability.

Printed in Canada CPB-0360 (2011-09/750)



# CAMOPLAST **FLEXHAUL**

## PULL-BEHIND TRACK SYSTEMS

## HARVEST CARTS



### FLEXHAUL track system benefits:

- 60 - 70 % ground pressure reduction versus tires
- Large contact area combined with patented undercarriage system for improved stability
- 70 series offers shorter wheelbase compatible with wheeled tractors
- Narrow track widths available for controlled traffic applications
- Tread pattern designed for minimal soil disturbance and low vibration

Flexhaul model	Wheelbase (in)	Overall height (in)	Overall length (in)	# of bogie axles	Ground contact per pair (in <sup>2</sup> )	Capacity per pair (lbs)
70-3002	75.5	37.0	112.5	2	4,530	70,000
70-3601	66.5	38.0	104.5	2	4,788	70,000
80-2503	107.5	38.0	145.5	4	5,375	80,000
80-3003	107.5	38.0	145.5	4	6,450	80,000
100-3602	107.5	39.0	146.5	4	7,740	100,000
100-3603*	98.5	39.0	137.5	4	7,092	100,000

\*Available soon

## SPRAYERS



### FLEXHAUL track system benefits:

- 14" - 18" track widths available for several row crop applications
- 70 - 80 % ground pressure reduction versus tires
- Large contact area combined with patented undercarriage system for improved stability
- Independent movement of undercarriages for greater terrain following capabilities
- Tread patterns designed for minimal soil disturbance

Flexhaul model	Wheelbase (in)	Overall height (in)	Overall length (in)	# of bogie axles	Ground contact per pair (in <sup>2</sup> )	Capacity per pair (lbs)
30-1401	46.5	36.5	83.0	1	1,349	30,000
30-1601	46.5	36.5	83.0	1	1,535	30,000
30-1602	40.5	34.5	75.0	1	1,337	30,000
40-1402	72.5	37.5	110.0	2	2,103	40,000
45-1603	72.5	37.5	110.0	2	2,393	45,000
45-1801	72.5	37.5	110.0	2	2,610	45,000
60-1604	104.5	38.0	142.5	4	3,449	60,000
60-1802	104.5	38.0	142.5	4	3,762	60,000

## FERTILIZER CARTS



### FLEXHAUL track system benefits:

- 16" - 25" track widths available for fertilizer caddy systems
- 30" - 36" track widths available for large capacity spreaders
- 60+ % ground pressure reduction versus tires
- Large contact area combined with patented undercarriage system for improved stability
- Tread patterns designed for minimal soil disturbance and low vibration

Flexhaul model	Wheelbase (in)	Overall height (in)	Overall length (in)	# of bogie axles	Ground contact per pair (in <sup>2</sup> )	Capacity per pair (lbs)
30-1602	40.5	34.5	75.0	1	1,337	30,000
45-1603	72.5	37.5	110.0	2	2,393	45,000
45-1801	72.5	37.5	110.0	2	2,610	45,000
60-1604	104.5	38.0	142.5	4	3,449	60,000
60-1802	104.5	38.0	142.5	4	3,762	60,000
70-3002	75.5	37.0	112.5	2	4,530	70,000
80-2503	107.5	38.0	145.5	4	5,375	80,000
100-3602	107.5	39.0	146.5	4	7,740	100,000
100-3603*	98.5	39.0	137.5	4	7,092	100,000

\*Available soon

## PLANTERS, STRIP TILL, SEED CARTS



### FLEXHAUL track system benefits:

- 16" - 25" track widths available for several row crop configurations
- 30 - 60 % ground pressure reduction versus tires
- Shorter wheelbase reduces berming at the headlands
- Minimize pinch row effects with 2 x track system
- Gauge setting options available depending on planter model
- Tread patterns designed for minimal soil disturbance for operation in the furrow or over the planting row
- Increase mobility through soft footing conditions

Flexhaul model	Wheelbase (in)	Overall height (in)	Overall length (in)	# of bogie axles	Ground contact per pair (in <sup>2</sup> )	Capacity per pair (lbs)
30-1601	46.5	36.5	83.0	1	1,535	30,000
30-1602	40.5	34.5	75.0	1	1,337	30,000
35-2201	40.5	34.5	75.0	1	1,782	35,000
35-2501	40.5	34.5	75.0	1	2,025	35,000
40-2502	46.5	36.5	83.0	1	2,325	40,000
70-3001	66.5	37.0	103.5	2	3,990	70,000
70-3601	66.5	38.0	104.5	2	4,788	70,000